

Model :

Tyremate 200 TL
Tyremate 200 TL - RFT



» Fully Automatic «
Run Flat Tyre

- Suitable for Car and LCV tyres
- Capable of handling stiff, wide and low-profile tyres using RFT helper arm
- Pneumatically operated tilting type vertical column
- Pneumatically operated twin cylinders for firm clamping
- Individual pedal for vertical column tilting
- Alloy wheel plastic protector for jaws

Model :

Tyremate 200 TL 26
Tyremate 200 TL 26 - RFT



» Fully Automatic «
Tubeless

- Suitable for Car and LCV tyres
- Pneumatically operated tilting type vertical column
- Pneumatically operated twin cylinders for firm clamping
- Individual pedal for vertical column tilting
- Four Jaw self centering chuck
- Alloy wheel plastic protector for jaws

Model :

TC - XL - 40
TC - XL - 40+



» Semi Automatic «

- Suitable for Car and LCV tyres
- Pneumatically operated twin cylinders for firm clamping
- Four Jaw self centering chuck
- Horizontal moving arm
- Alloy wheel plastic protector for jaws

Technical Specification

Technical Specification	Tyremate 200 TL Tyremate 200 TL - RFT	Tyremate 200 TL 26 Tyremate 200 TL 26 - RFT	TC - XL - 40	TC - XL - 40+
Rim clamping from inside	12" – 24" (305 – 610 mm)	14" - 26" (356 - 660 mm)	12" – 21" (305 – 533 mm)	14" – 26" (356 – 660 mm)
Rim clamping from outside	10" – 21" (254 – 533 mm)	12" – 24" (305 - 610 mm)	10" – 18" (254 – 457 mm)	12" – 24" (305 – 610 mm)
Max. wheel diameter	38" (965 mm)	43" (1092 mm)	37" (940 mm)	41" (1041 mm)
Max. wheel width	3" – 12" (76 – 305 mm)	15" (381 mm)	3" - 12" (76 - 305 mm)	16" (406 mm)
Operating pressure	8 – 10 bar	6 – 8 bar	6 – 8 bar	6 – 8 bar
Bead breaker force	2500 kg	2500 kg	2500 kg	2500 kg
Power supply	220V AC, Single Phase, 50 Hz	220V AC, Single Phase, 50 Hz	220V AC, Single Phase, 50 Hz	220V AC, Single Phase, 50 Hz
Power	1.5 HP	1.5 HP	1.0 HP	1.5 HP

Standard Accessories



Optional Accessories

